

Mounted Offset Disc Harrow

Code: A-MODH



AGROVISION 'Mounted Heavy Duty Disc Harrow' is used in open farm working for the superficial ploughing, for the shattering of clods, preparation of soil for sowing, burial of organic substances & Remains. When mounted on a tractor, becomes a compact unit that can easily be manoeuvred into corners or on short head lands. In addition, the implement being easily attached and transportable in top speeds, little time is lost between the shed and the field.

Advantage

- » AGROVISION MOUNTED OFFSET DISC HARROW is used in open farm workings for the superficial ploughing, for the shattering of clods, preparation of soil for sowing, burial of organic substances & remains.
- » To air the soil and to eliminate the weeds.
- » For breaking the roots.

Features

- » High quality Boron steel discs.
- » Tillage depth of the harrow is 6 inch.
- » Easily transportable- as it gets easily attached and mounted.
- » Maintenance is easy but need to be scheduled.

Technical Specification

MODEL	A-MODH6 X 6	A-MODH7 X 7	A-MODH8 X 8	A-MODH9 x 9	A-MODH10 x 10
NO. OF DISCS	12	14	16	18	20
FRAME	75 x10mm Angle with 100 x 50 mm Channel	75 x10mm Angle with 100 x 50 mm Channel	75 x10mm Angle with 100 x 50 mm Channel	75 x10mm Angle with 100 x 50 mm Channel	75 x10mm Angle with 100 x 50 mm Channel
GANG BOLT	32 mm Central square	32 mm Central square	32 mm Central square	32 mm Central square	32 mm Central square
	Solid Bar	Solid Bar	Solid Bar	Solid Bar with split gangs	Solid Bar with split gangs
LENGTH	2030 mm	2080 mm	2130 mm	2230 mm	2280 mm
HEIGHT	1150 mm with 560mm Disc	1150 mm with 560mm Disc	1150 mm with 560mm Disc	1150 mm with 560mm Disc	1150 mm with 560mm Disc
	1200mm with 610mm Disc	1200mm with 610mm Disc	1200mm with 610mm Disc	1200mm with 610mm Disc	1200mm with 610mm Disc
DISTANCE BETWEEN DISCS	225 mm	225 mm	225 mm	225 mm	225 mm
MOUNTING	CAT. I/ II (Optional)	CAT. I/ II (Optional)	CAT. I/ II (Optional)	CAT. I/ II (Optional)	CAT. I/ II (Optional)
DISC DIAMETER (mm)	560/610 (Optional)	560/610 (Optional)	560/610 (Optional)	560/610 (Optional)	560/610 (Optional)
TYPE OF DISCS	Notched in Front	Notched in Front	Notched in Front	Notched in Front	Notched in Front
	& Plain in Rear	& Plain in Rear	& Plain in Rear	& Plain in Rear	& Plain in Rear
BEARING HUBS (Nos.)	4	4	6	8 (Split Gang Arrangement)	8 (Split Gang Arrangement)
WIDTH OF CUT	1350-1400 mm	1600-1650 mm	1800-1850 mm	2000-2100 mm	2250-2300 mm
POWER REQUIRED	35 HP	40-45 HP	45-50 HP	50-55 HP	55-60 HP
APPROX WEIGHT (KG)	425with 610 mm Disc 400 with 560 mm Disc	465with 610 mm Disc 450 with 560 mm Disc	510 with 610 mm Disc 480 with 560 mm Disc	570with 610 mm Disc 540 with 560 mm Disc	625with 610 mm Disc 575 with 560 mm Disc

NOTE:-The contents of this website are only giving information to the end user without engagement from our side. The company can modify specifications of the total machine and it's components without any previous notice.

Available Colors :



Manufactured By:- **INDIA AGROVISION IMPLEMENTS PVT. LTD.** (ISO 9001 : 2008 Certified Company)
P.No: Pa 010-007 & Pa 010-008, Light Eng. Zone Mahindra World City Jaipur, Rajasthan - 302 037 (India)
Phone : +91-9636494375, +91-9929052289 Website : www.indiaagrovision.com Email : india.agrovision@gmail.com