

FLAIL MOWER / MULCHER

AGROVISION



Manual Side Shift Flail Mower

www.indiaagrovision.com

Features



Side Shift Three-point linkage with Max. 300 mm shift, CAT - I & II to connect the various tractor models.

Gear box with an input Speed of 540 RPM.




The front safety flaps made of steel allow material to enter the cutting frame but prevent inside objects from being expelled outside at high operating speed.

Features



3 Belts & 4 belts (BX Type) transmission to transfer power to the rotor.

Standard “Y” & “I” type blades and as an option Hammer blades.



A pair of protective skid prevents wear to the machine & allow the operator to adjust the cutting height.

Specifications

MODEL	A-FM 145/MSS
HITCH	Cat- I / II
OVERALL WIDTH	1620 mm
WORKING WIDTH	1450 mm
GEAR BOX	Free Wheel Gear Box
MANUAL SIDE SHIFT	300 mm (Max.)
PTO INPUT SPEED	540 RPM
SIDE TRANSMISSION TYPE	4 Belts (BX Type)
NO. OF BLADES (Y & I TYPE)	36 + 18
NO. OF HAMMERS	18
APPROX. WEIGHT	560 Kg.
REQUIRED TRACTOR	40 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.

Specifications

MODEL	A-FM 160/MSS
HITCH	Cat- I / II
OVERALL WIDTH	1770 mm
WORKING WIDTH	1600 mm
GEAR BOX	Free Wheel Gear Box
MANUAL SIDE SHIFT	300 mm (Max.)
PTO INPUT SPEED	540 RPM
SIDE TRANSMISSION TYPE	4 Belts (BX Type)
NO. OF BLADES (Y & I TYPE)	40 + 20
NO. OF HAMMERS	20
APPROX. WEIGHT	620 Kg.
REQUIRED TRACTOR	40 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.

Specifications

MODEL	A-FM 175/MSS
HITCH	Cat- I / II
OVERALL WIDTH	1920 mm
WORKING WIDTH	1750 mm
GEAR BOX	Free Wheel Gear Box
MANUAL SIDE SHIFT	300 mm (Max.)
PTO INPUT SPEED	540 RPM
SIDE TRANSMISSION TYPE	4 Belts (BX Type)
NO. OF BLADES (Y & I TYPE)	44 + 22
NO. OF HAMMERS	22
APPROX. WEIGHT	660 Kg.
REQUIRED TRACTOR	50 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.

Specifications

MODEL	A-FM 205/MSS
HITCH	Cat- I / II
OVERALL WIDTH	2220 mm
WORKING WIDTH	2050 mm
GEAR BOX	Free Wheel Gear Box
MANUAL SIDE SHIFT	300 mm (Max.)
PTO INPUT SPEED	540 RPM
SIDE TRANSMISSION TYPE	4 Belts (BX Type)
NO. OF BLADES (Y & I TYPE)	52 + 26
NO. OF HAMMERS	26
APPROX. WEIGHT	715 Kg.
REQUIRED TRACTOR	50 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.

Specifications

MODEL	A-FM 220/MSS
HITCH	Cat- I / II
OVERALL WIDTH	2370 mm
WORKING WIDTH	2200 mm
GEAR BOX	Free Wheel Gear Box
MANUAL SIDE SHIFT	300 mm (Max.)
PTO INPUT SPEED	540 RPM
SIDE TRANSMISSION TYPE	4 Belts (BX Type)
NO. OF BLADES (Y & I TYPE)	56 + 28
NO. OF HAMMERS	28
APPROX. WEIGHT	780 Kg.
REQUIRED TRACTOR	50 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.