

# FLAIL MOWER / MULCHER



**Flail Mower / Mulcher**

[www.indiaagrovision.com](http://www.indiaagrovision.com)

# Features



Three-point linkage of CAT - I & II to connect the various tractor models.

Gear Box with an input speed of 540 RPM.




The front safety flaps made of steel allow material to enter the cutting frame but prevent inside objects from being expelled outside at high operating speed.

# Features



3 Belts & 4 Belts (BX type) transmission to transfer power to the rotor.

Standard “Y” & “I” type blades and as an option Hammer blades.



A pair of protective skid prevents wear to the machine & allow the operator to adjust the cutting height.

# Specifications

<b>MODEL</b>	<b>A-FM 115</b>
<b>HITCH</b>	Cat- I / II
<b>OVERALL WIDTH</b>	1300 mm
<b>WORKING WIDTH</b>	1150 mm
<b>GEAR BOX</b>	Free Wheel Gear Box
<b>PTO INPUT SPEED</b>	540 RPM
<b>SIDE TRANSMISSION TYPE</b>	3 Belts (BX Type)
<b>NO. OF BLADES (Y &amp; I TYPE)</b>	28 + 14
<b>NO. OF HAMMERS</b>	14
<b>APPROX. WEIGHT</b>	450 Kg.
<b>REQUIRED TRACTOR</b>	25 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.

# Specifications

<b>MODEL</b>	<b>A-FM 130</b>
<b>HITCH</b>	Cat- I / II
<b>OVERALL WIDTH</b>	1450 mm
<b>WORKING WIDTH</b>	1300 mm
<b>GEAR BOX</b>	Free Wheel Gear Box
<b>PTO INPUT SPEED</b>	540 RPM
<b>SIDE TRANSMISSION TYPE</b>	3 Belts (BX Type)
<b>NO. OF BLADES (Y &amp; I TYPE)</b>	32 + 16
<b>NO. OF HAMMERS</b>	16
<b>APPROX. WEIGHT</b>	490 Kg.
<b>REQUIRED TRACTOR</b>	40 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.

# Specifications

<b>MODEL</b>	<b>A-FM 145</b>
<b>HITCH</b>	Cat- I / II
<b>OVERALL WIDTH</b>	1620 mm
<b>WORKING WIDTH</b>	1450 mm
<b>GEAR BOX</b>	Free Wheel Gear Box
<b>PTO INPUT SPEED</b>	540 RPM
<b>SIDE TRANSMISSION TYPE</b>	4 Belts (BX Type)
<b>NO. OF BLADES (Y &amp; I TYPE)</b>	36 + 18
<b>NO. OF HAMMERS</b>	18
<b>APPROX. WEIGHT</b>	535 Kg.
<b>REQUIRED TRACTOR</b>	40 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.

# Specifications

<b>MODEL</b>	<b>A-FM 160</b>
<b>HITCH</b>	Cat- I / II
<b>OVERALL WIDTH</b>	1770 mm
<b>WORKING WIDTH</b>	1600 mm
<b>GEAR BOX</b>	Free Wheel Gear Box
<b>PTO INPUT SPEED</b>	540 RPM
<b>SIDE TRANSMISSION TYPE</b>	4 Belts (BX Type)
<b>NO. OF BLADES (Y &amp; I TYPE)</b>	40 + 20
<b>NO. OF HAMMERS</b>	20
<b>APPROX. WEIGHT</b>	575 Kg.
<b>REQUIRED TRACTOR</b>	40 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.

# Specifications

<b>MODEL</b>	<b>A-FM 175</b>
<b>HITCH</b>	Cat- I / II
<b>OVERALL WIDTH</b>	1920 mm
<b>WORKING WIDTH</b>	1750 mm
<b>GEAR BOX</b>	Free Wheel Gear Box
<b>PTO INPUT SPEED</b>	540 RPM
<b>SIDE TRANSMISSION TYPE</b>	4 Belts (BX Type)
<b>NO. OF BLADES (Y &amp; I TYPE)</b>	44 + 22
<b>NO. OF HAMMERS</b>	22
<b>APPROX. WEIGHT</b>	615 Kg.
<b>REQUIRED TRACTOR</b>	50 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.



# Specifications

<b>MODEL</b>	<b>A-FM 205</b>
<b>HITCH</b>	Cat- I / II
<b>OVERALL WIDTH</b>	2220 mm
<b>WORKING WIDTH</b>	2050 mm
<b>GEAR BOX</b>	Free Wheel Gear Box
<b>PTO INPUT SPEED</b>	540 RPM
<b>SIDE TRANSMISSION TYPE</b>	4 Belts (BX Type)
<b>NO. OF BLADES (Y &amp; I TYPE)</b>	52 + 26
<b>NO. OF HAMMERS</b>	26
<b>APPROX. WEIGHT</b>	660 Kg.
<b>REQUIRED TRACTOR</b>	50 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative.

# Specifications

<b>MODEL</b>	<b>A-FM 220</b>
<b>HITCH</b>	Cat- I / II
<b>OVERALL WIDTH</b>	2370 mm
<b>WORKING WIDTH</b>	2200 mm
<b>GEAR BOX</b>	Free Wheel Gear Box
<b>PTO INPUT SPEED</b>	540 RPM
<b>SIDE TRANSMISSION TYPE</b>	4 Belts (BX Type)
<b>NO. OF BLADES (Y &amp; I TYPE)</b>	56 + 28
<b>NO. OF HAMMERS</b>	28
<b>APPROX. WEIGHT</b>	700 Kg.
<b>REQUIRED TRACTOR</b>	50 - 80 HP

• Agrovision reserves the right to improve and or modify the technical features of this product without prior notice. The images in this publication are merely illustrative..